

TDB-ACC-NO: NN8907370

DISCLOSURE Breakpoint Bit Technique for an Address Compare
TITLE: Function

PUBLICATION-DATA: IBM Technical Disclosure Bulletin, July 1989, US

VOLUME NUMBER: 32

ISSUE NUMBER: 2

PAGE NUMBER: 370 - 371

PUBLICATION-DATE: July 1, 1989 (19890701)

CROSS REFERENCE: 0018-8689-32-2-370



DISCLOSURE TEXT:

- This article describes a technique which provides a breakpoint function in a processor without the use of extra comparison logic and with minimal delay. - A circuit designed for tracing the address flow of a processor (microprocessor, digital signal processor, etc.) must make an address comparison to begin or stop a trace. To do this a trigger address or breakpoint is usually written to a breakpoint register. This register is periodically compared to the address on the processor's address bus. If a match is detected by a comparator circuit, a breakpoint is found and the address trace logic can begin or halt a trace. This same technique is typically used in stop-on-address circuits to halt a processor at a given address. - The logic required to perform a breakpoint detection typically consists of a breakpoint register and a comparator as shown in Fig. 1. The size of the breakpoint register and comparator depends on the size of the address bus being monitored. For example, on a 14-bit address bus, the register and comparator could easily take up over 100 logic gates if implemented in very large-scale integration (VLSI). - The faster the processor, the faster the comparison must be made. This is extremely important when monitoring very fast processors such as digital signal processors. ***** SEE ORIGINAL DOCUMENT ***** Fig. 2 illustrates the technique of this disclosure wherein a 14-bit address bus of a digital signal processor (DSP) is monitored. This DSP has a separate instruction address bus and data address bus. The instructions are stored in a 27-bit wide instruction memory which is randomly accessible (RAM). Aside from the 27 bits, this RAM has an extra bit added. This bit is called the breakpoint bit. Wherever a

breakpoint is desired, the breakpoint bit at that particular memory address, is set. The extra bit in RAM is not extra overhead due to standard RAM sizes. In fact, this takes advantage of previously unused RAM bits. - As the DSP runs, it fetches instructions from instruction RAM. As instructions are fetched, the breakpoint bit is tested. If the breakpoint bit is found to be set, an 'address compare' function has been realized without the extra logic and time delay inherent to conventional address compare circuits. - Another feature of this design is the ability to have not one, but several breakpoints, without adding any additional logic. Multiple breakpoints is a valuable feature that would require several additional registers if it were implemented in a conventional address compare circuit.

SECURITY: Use, copying and distribution of this data is subject to the restrictions in the Agreement For IBM TDB Database and Related Computer Databases. Unpublished - all rights reserved under the Copyright Laws of the United States. Contains confidential commercial information of IBM exempt from FOIA disclosure per 5 U.S.C. 552(b)(4) and protected under the Trade Secrets Act, 18 U.S.C. 1905.

COPYRIGHT STATEMENT: The text of this article is Copyrighted (c) IBM Corporation 1989. All rights reserved.



ADVANCED 80386 PROGRAMMING TECHNIQUES

James L. Turley

**Osborne McGraw-Hill
Berkeley, California**

Osborne McGraw-Hill
2600 Tenth Street
Berkeley, California 94710
U.S.A.

For information on translations and book distributors outside of the U.S.A., please write to Osborne McGraw-Hill at the above address.

A complete list of trademarks appears on page 499.

Advanced 80386 Programming Techniques

Copyright ©1988 by McGraw-Hill, Inc. All rights reserved. Printed in the United States of America. Except as permitted under the Copyright Act of 1976, no part of this publication may be reproduced or distributed in any form or by any means, or stored in a database or retrieval system, without the prior written permission of the publisher, with the exception that the program listings may be entered, stored, and executed in a computer system, but they may not be reproduced for publication.

234567890 DODO 898

ISBN 0-07-881342-5

Information has been obtained by Osborne McGraw-Hill from sources believed to be reliable. However, because of the possibility of human or mechanical error by our sources, Osborne McGraw-Hill, or others, Osborne McGraw-Hill does not guarantee the accuracy, adequacy, or completeness of any information and is not responsible for any errors or omissions or the results obtained from use of such information.